

RS1AD THRU RS1MD

SURFACE MOUNT FAST RECOVERY RECTIFIERS

Reverse Voltage - 50 to 1000 V

Forward Current - 1 A


Features

- High current capability
- High surge current capability
- High reliability
- Low reverse current
- Fast switching for high efficiency

Mechanical Data

- **Case:** SMA (DO-214AC) molded plastic
- **Mounting position:** Any
- **Lead:** Lead formed for surface mount
- **Polarity:** Color band denotes cathode end

SMA (DO-214AC)



Dimensions in inches and (millimeters)

Absolute Maximum Ratings and Characteristics


Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbols	RS1AD	RS1BD	RS1DD	RS1GD	RS1JD	RS1KD	RS1MD	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current at $T_L = 90^\circ\text{C}$	$I_{F(AV)}$	1							A
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	30							A
Maximum Forward Voltage at 1 A	V_F	1.3							V
Maximum DC Reverse Current at $T_A = 25^\circ\text{C}$ at Rated DC Blocking Voltage at $T_A = 100^\circ\text{C}$	I_R	5							μA
		50							
Maximum Reverse Recovery Time ¹⁾	t_{rr}	150			250	500			ns
Typical Junction Capacitance ²⁾	C_J	15							pF
Typical Thermal Resistance ³⁾	$R_{\theta JA}$	50							$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_{stg}	- 65 to + 150							$^\circ\text{C}$

¹⁾ Reverse recovery test conditions $I_F = 0.5\text{ A}$, $I_R = 1\text{ A}$, $t_{rr} = 0.25\text{ A}$.

²⁾ Measured at 1 MHz and applied reverse voltage of 4 V.

³⁾ P.C.B. mounted with 0.2 X 0.2" (5 X 5 mm) copper pad areas.










SEMTECH ELECTRONICS LTD.



Dated : 09/12/2014 GD Rev:03

RS1AD THRU RS1MD



SEMTECH ELECTRONICS LTD.



ISO 9001:2008
Certificate No. 50713410

ISO 14001:2004
Certificate No. 7116

BS-OHSAS 18001:2007
Certificate No. 7116

IECQ QC 080000
Certificate No. PFC-HSPM-468-1

ISO 9001:2008
Certificate No. 50713410

Dated : 09/12/2014 GD Rev:03